

Ilford Delta-400 - 21 °C

NOTE : Une fourchette d'exposition située entre EI 250/25 et EI 500/28 est conseillée.

Ilford Delta-400 à EI 800/30°

ADOX	Adonal 1+25											
21 °C	cf 24 °C											
AGFA	Rodinal 1+25											
21 °C	cf 24 °C											
AMALOCO	AM-74 1+7	AM-74 1+9	AM-74 1+15	AM-74 1+19								
21 °C	09.30	-	12.30	19.00								
ARS-IMAGO	FD 1+39											
21 °C	cf 20 °C											
BAK	Acufine											
21 °C	12.15											
CLAYTON	F60 1+9	F76 plus 1+9										
21 °C	09.30	09.00										
FOMA	R09 New 1+25											
21 °C	cf 24 °C											
ILFORD	ID-11 pur	ID-11 1+1	Microphen pur	Microphen 1+1	Ilfotec LC29 1+19	Ilfotec LC29 1+29	Ilfotec DDX 1+4	Ilfotec HC 1+15	Ilfotec HC 1+31	Ilfosol-S 1+9	Ilfosol-S 1+14	
21 °C	11.00	16.45	08.00	14.45	09.30	15.30	09.45	05.15	09.30	13.30	cf 24 °C	
(suite)	Ilfosol-3 1+9	Ilfosol-3 1+14										
21 °C	13.15	19.30										
KODAK	D-76 pur	D-76 1+1	TMAX-dev 1+4	HC-110 (A) 1+15	HC-110 (B) 1+31	XTOL	XTOL 1+1					
21 °C	11.00	16.45	08.15	05.15	09.30	09.30	10.45					
SPURSINN	SAM classic 1+5	SAM classic 1+7										
21 °C	12.00	15.45										
TETENAL	Ultrafin SF	Ultrafin SF 1+1	Ultrafin plus 1+4									
21 °C	12.30	cf 24 °C	11.15									

LÉGENDE :
vert : temps autres températures que 20° C modifiés par coefficient
or : temps autres températures que 20° C donnés par les fabricants